

## Setup Sheet for Team Associated's SC8

Rev. 1

### :: Front Suspension

anti-roll bar:  
 2.2 - black  
 2.5 - silver  
 2.8 - gold

front body  
 mount hole



steering rack:  
 back  
 mid  
 front

hinge pin  
 bushing

# \_\_\_\_\_  
 up  down

camber: \_\_\_\_\_

caster: \_\_\_\_\_

toe: \_\_\_\_\_

ride height: \_\_\_\_\_

kickup bushing

# \_\_\_\_\_  
 up  down

### :: Rear Suspension

anti-roll bar:  
 2.2 - black  
 2.5 - silver  
 2.8 - gold

wheelbase:  
 long  
 medium  
 short

rear body  
 mount hole



camber: \_\_\_\_\_

toe: \_\_\_\_\_

hub:  
 upper  
 lower

ride height: \_\_\_\_\_

anti-squat  
 bushing

# \_\_\_\_\_  
 up  down

### :: Front Shocks

spring: \_\_\_\_\_ piston: \_\_\_\_\_  
 shock fluid: \_\_\_\_\_ length: \_\_\_\_\_  
 shock cap: \_\_\_\_\_

### :: Rear Shocks

spring: \_\_\_\_\_ piston: \_\_\_\_\_  
 shock fluid: \_\_\_\_\_ length: \_\_\_\_\_  
 shock cap: \_\_\_\_\_

### :: Differentials

front fluid: \_\_\_\_\_  
 center fluid: \_\_\_\_\_  
 rear fluid: \_\_\_\_\_

### :: Wing

location:  forward  back  
 angle:  low  med.  high  
 type: \_\_\_\_\_

### :: Chassis Braces

standard  molded  aluminum

other: \_\_\_\_\_  
 \_\_\_\_\_

### :: Engine

engine: \_\_\_\_\_ restrictor: \_\_\_\_\_  
 muffler: \_\_\_\_\_ temp: \_\_\_\_\_  
 glow plug: \_\_\_\_\_  
 fuel: \_\_\_\_\_

### :: Gearing/Clutch

gearing: \_\_\_\_\_  
 shoes: \_\_\_\_\_ x aluminum \_\_\_\_\_ x fiber  
 spring: \_\_\_\_\_ x .9mm \_\_\_\_\_ x 1.0mm \_\_\_\_\_ x 1.1mm  
 notes: \_\_\_\_\_

### :: Notes

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

### :: Tires

tire (F/R): \_\_\_\_\_ / \_\_\_\_\_  
 compound (F/R): \_\_\_\_\_ / \_\_\_\_\_  
 insert: \_\_\_\_\_ wheel: \_\_\_\_\_

### :: Race and Vehicle Comments

qualify: \_\_\_\_\_ main: \_\_\_\_\_ finish: \_\_\_\_\_ tq:   
 comments: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

### :: Track Info

traction:  high  med.  low  
 surface:  smooth  bumpy  
 blue groove  soft dirt  grass  
 clay  wet  dusty  
 other: \_\_\_\_\_  
 \_\_\_\_\_