

SET-UP SHEET

XRAY T2.0N9

RACE			
TRACK			
NAME			
CITY / COUNTRY			
CONTACT			

DATE	TEMPERATURE / °F or °C	AIR	TRACK
QUALIFYING POSITION	BEST LAPTIME / sec	FINAL POSITION	RACE LENGTH / minutes

TRACK CONDITION	<input type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT
	<input type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED
	<input type="checkbox"/> FAST	
TRACTION	<input type="checkbox"/> LOW	<input type="checkbox"/> MEDIUM
	<input type="checkbox"/> HIGH	

FRONT	REAR
TRANSMISSION	

FRONT PULLEY	REAR PULLEY
DIFF.	
<input type="checkbox"/> LOOSE <input type="checkbox"/> MEDIUM <input type="checkbox"/> TIGHT	<input type="checkbox"/> LOOSE <input type="checkbox"/> MEDIUM <input type="checkbox"/> TIGHT
ONE WAY DIFFERENTIAL	<input type="checkbox"/> YES
SOLID ONE WAY DIFF.	<input type="checkbox"/> YES
SOLID AXLE	<input type="checkbox"/> YES
MIDDLE ONE WAY PULLEY	
FIXED	<input type="checkbox"/>
ONE-WAY	<input type="checkbox"/>

PINION / T	SPUR GEAR / T
FINAL DRIVE RATIO	ROLLOUT

FRONT	REAR
<input type="checkbox"/> ALU	<input type="checkbox"/> PLASTIC
SHOCKS	
XRAY SPRINGS	
#308393 Super Soft	<input type="checkbox"/> YELLOW (D=1.4) 14 lb
#308384	<input type="checkbox"/> BLUE-GREEN (D=1.5) 15 lb
#308394 Soft	<input type="checkbox"/> WHITE (D=1.5) 17.5 lb
#308385	<input type="checkbox"/> LIGHT-BLUE (D=1.6) 20 lb
#308395 Soft Medium	<input type="checkbox"/> BLUE (D=1.6) 22.5 lb
#308386	<input type="checkbox"/> DARK-BLUE (D=1.7) 25 lb
#308396 Medium	<input type="checkbox"/> VIOLET (D=1.7) 28 lb
#308387	<input type="checkbox"/> LIGHT-PURPLE (D=1.8) 30 lb
#308397 Medium Hard	<input type="checkbox"/> PURPLE (D=1.8) 33 lb
#308388	<input type="checkbox"/> LIGHT-RED (D=1.9) 35 lb
#308398 Hard	<input type="checkbox"/> RED (D=1.9) 38 lb

#308373	<input type="checkbox"/> C 2.2
#308374	<input type="checkbox"/> C 2.4
#308375	<input type="checkbox"/> C 2.6
#308376	<input type="checkbox"/> C 2.8
#308377	<input type="checkbox"/> C 3.0
#308378	<input type="checkbox"/> C 3.2
#308379	<input type="checkbox"/> C 3.4

OTHER SPRING	
OIL / CST	
LENGTH / mm	
PRELOAD / mm	
REBOUND %	
FOAM INSERTS	<input type="checkbox"/> YES <input type="checkbox"/> NO
O-RING ON SHAFT	<input type="checkbox"/> YES <input type="checkbox"/> NO

<input type="radio"/> OPENED	<input type="radio"/> CLOSED
HOLES IN PISTON	

ANTI-ROLL BAR	
THICKNESS / mm	THICKNESS / mm

TIRES	
DIAMETER / mm	
INSERTS	
ADDITIVE	

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT
------------	-------------	--------------	-----------	------------

WHEELS	
S <input type="checkbox"/> M <input type="checkbox"/> H <input type="checkbox"/>	HARDNESS

MOTOR	ARMATURE
	+ SPRING -
	+ BRUSH COMP. -

ESC	BATTERIES
BRUSHLESS	PROGRAM
	PUNCH
	INITIAL BRAKE
	AUTO BRAKE

BODY	WING
-------------	-------------

● - APPLIED S-SOFT M-MEDIUM H-HARD

