

NAME		TEMP	°C	ENGINE		MUFFLER		MANIFOLD
DATA		HUMIDITY	%	HEAD CLEARANCE	mm	FUEL TYPE		
TRACK		TRACTION	%	PLUG No.		RADIO		

SHOCK OIL	300 350 400 450 500 550 600 700
SHOCK PISTON	
SPRING	
SPRING ADJUSTER	mm
SHOCK POS	IN CENTER OUT
CASTER ANGLE	mm
CAMBER ANGLE	OG/1G 0 0.5 1.0 1.5 2.0
TOE ANGLE	mm
FRONT WIDTH	mm
REBOUND STOP	mm
STABILIZER BAR	
DIFF./ONEWAY	
DIFF OIL	#
GROUND CLEARANCE	mm
Servo Saver	10 11 12

SPACER	CASTER	ANGLE
4mm	6°	
3mm	8°	
2mm	10°	
1mm	12°	
0mm	14°	

SHOCK OIL	300 350 400 450 500 550 600 700
SHOCK PISTON	
SPRING	
SPRING ADJUSTER	mm
SHOCK POS	Upper: In - Center - Out Lower: U - L
Upper Arm POS	Inside: U - L Outside: U - L
CAMBER ANGLE	OG/1G 0 0.5 1.0 1.5 2.0 2.5 3.0
TOE ANGLE	
REAR WIDTH	mm
REBOUND STOP	mm
STABILIZER BAR	SILVER BLACK GOLD
DIFF	
DIFF OIL	#
TIRE TYPE	
TIRE SIZE	
GROUND CLEARANCE	mm

GEAR		CLUCH SHOE		BODY	
GEAR		CLUCH SPRING		SIDE PULLEY	25 26 27

memo.	Use Option Parts
-------	------------------