

NAME	TEMP	°C	ENGINE	MUFFLER
DATE	HUMIDITY	%	HEAD CLEARANCE	mm
TRACK	TRACTION	%	PLUG No.	RADIO

CASTER	ANGLE
2mm	8.5°
1mm	10.5°
0mm	12.5°

SERVO SAVER	9	10
SERVO ANGLE	%	
UPPER ARM POSITION	⊙ ⊙ ⊙ ⊙ ⊙ ⊙	
KNUCKLE ARM SPACER	mm	
KNUCKLE ARM TYPE	0°	1° 2°
DIFF()	/ ONE WAY / RIGID	

SHOCK OIL	300 350 400 450 500 550 600
SHOCK TYPE	N / VZ075
DIAPHRAGM	N
SHOCK PISTON	N
SPRING	N
SPRING ADJUSTER	mm
SHOCK POSITION	1 2 3
CASTER ANGLE	mm
CAMBER ANGLE	L 0 0.5 1 1.5 2 2.5 3
	R 0 0.5 1 1.5 2 2.5 3
TOE ANGLE	
FRONT WIDTH	mm
UP STOP	mm
DOWN STOP	mm
ANTIROLL BAR	有 VZ084S ⊙ ⊙ ⊙ ⊙ ⊙ 無 VZ084 ⊙ ⊙ ⊙ ⊙ ⊙
TIRE TYPE & HARDNESS	
INNER FOAM	
WHEEL TYPE	
CHASSIS HEIGHT	mm

GEAR	TOTAL	GEAR	TOTAL	GEAR	TOTAL	GEAR	TOTAL	GEAR	TOTAL
15	61	8	13	15	60	8	00	15	59
16	61	7	63	16	60	7	50	16	59
17	61	7	18	17	60	7	06	17	59
								22	56
								23	56
								20	55
								21	55
								22	55
								23	55

SHOCK OIL	N 300 350 400 450 500 550 600
SHOCK TYPE	N / VZ075
DIAPHRAGM	N
SHOCK PISTON	N
SPRING	N
SPRING ADJUSTER	mm
SHOCK POS	1 2 3 4
WHEEL SPACER	0mm / 2mm
UPPER ARM HEIGHT	mm IN/OUT
CAMBER ANGLE	L 0 0.5 1 1.5 2 2.5 3 3.5 4
	R 0 0.5 1 1.5 2 2.5 3 3.5 4
TOE ANGLE	
REAR WIDTH	mm
DOWN STOP	mm
ANTIROLL BAR	N 1.3/1.4
TIRE TYPE & HARDNESS	
INNER FOAM	
WHEEL TYPE	
CHASSIS HEIGHT	mm
LOWER ARM POSITION	⊙ ⊙ ⊙ ⊙ ⊙ ⊙
BODY	
WING HEIGHT	mm

FLYWHEEL	N	PINION GEAR	15 16 17 / 20 21 22 23
CLUCH SHOE	N / UM210	SPUR GEAR	59 60 61 / 55 56
CLUTCH SPRING		BRAKE	%
		REAR DIFF	

MEMO