

:: Driver:	:: Date:	
:: Track:		
:: Event:		

Setup Sheet for Team Associated's 10R5 0	VAL	Rev. 1
:: Front Suspension	:: Rear Suspension	
Kingpin Lube:Springs:LF:	RF:	2 screws 3 screws
Upper Arm Mounts:LF: 0° 5° 10 RF: 0° 5° 10		Center Shock
Camber:LF:RF:	Ride Height:	- Piston:
Ride Height:	Side Shocks	Oil:
Mounting Plate Riser:	Oil:LR: RR:	Spring:
Yes No Kingpin: shim qty/thickness, LF:RF:	Spring:LR: RR:	Position:
shim qty/thickness, LF:RF:		
Wheel axle shims: LF:RF:		
Lower arm Front ride spacing:LF: RF: spacers:		
Caster: LF:F thick thin thicky thick an		
LF: □1.80° □3.25° □ RF: □1.80° □3.25° □]6.15° Hub spacers:LR:]6.15° Notes:	/RR:
:: Tires	_	ery Placement
Tires LEFT RIGHT Total	al Car Weight:oz. Fro	nt Rear
Tire Compounds F R Tire Diameter F	Tweak Settingsozozozoz	
Tire Width F	Shade	in battery placement for cells / LiPo battery pack.
Tire Treatment Type:		y:
	of tire treatment ———	•
:: Track Info / Body	:: Motor/Speed Control	:: Transmitter
smooth: bumpy: hraction: high med. low	Motor:	Turning Circle: Steering Expo:
Body Type and Make:	Timing:Gear:/	_ Steering Expo: Brake E.P. :
Body Height:	E.S.C. : E.S.C. Settings:	Throttle Expo:
Wing:	, c.o.o. aetaliys	Notes:
Notes:		

:: For more setups, visit www.RC10.com and click on 'Racing'