	Setup	Sheet	Track:		
	-			Slick	Smooth
				Loose-Dirt	Rough
			Tight / DOpen	Blue-Groove	Extra-Rough
Front Suspension (Circle or Cheo	ck the Appropria	ate Settings)	Notes:		
	Bellcranks				
Ride Height	Rod	Length ock			
Camber 🗒 + °	Oti	her			
Caster Other °	\bigcirc			$\square 2$	
□ No Sway Bar □ Yes size		# of washe			
Front Shocks					
Oil:				Inside	
Piston: Distandard / Drille	ed				
Spring:				60,	
Limiters: Inside Outside		Ð			
Rear Suspension	lotes:				
Toe-In Outside					
Ride Height					
Camber 🛛 + °					
Pivot Support Do Shim Under Front D Shim Under Rear					
□ No Sway Bar □ Yes size			Hole in Rear Hub		
Rear Shocks				Hole in Bulkhead	
Oil:			5 4 3 2		
Piston: Standard / Drilled					
Spring:				Inside	876
Limiters: Dinside Dutside				<u>(</u>)	
Tires	Compound	Foam		Motor:	
Front:				Pinion:	
Rear:					
Clicker Adjustment: Locked One-Way:					
Battery Placement: Back Forward Other:					
Notes:					