SET-UP SH DATE: Image: Constraint of the second	
<i>TRACK:</i>	
FRONT SUSPENSION	(CIRCLE OR CHECK CORRECT SETTINGS)
TOE-IN / TOE-OUT:° FRONT RIDE HEIGHT:° FRONT CAMBER: +°	
NOTES:	# OF WASHERS INSIDE INSIDE INSIDE OUTSIDE OUTSIDE OUTSIDE OUTSIDE OUTSIDE
REAR SUSPENSIONPIVOT SUPPORT: \Box #2, \Box #4REAR HUB: \Box 3.5°, \Box 2.5°REAR RIDE HEIGHT:	
REAR CAMBER: -	HOLE IN HUB BULKHEAD
<u>REAR SHOCKS</u> OIL: PISTON: DRILLED / □ STANDARD SPRING: LIMITERS: INSIDE, OUTSIDE	OUTSIDE MIDDLE INSIDE O O O O O O O O O O O O O
TRANSMISSION & CHASSIS HYDRA-DRIVE: DNO, DYES - FLUID: DLIGHT, DSTD., DHEAVY	
	OLD, SILVER MOTOR: PINION GEAR:
CHASSIS: SHORT, STANDARD, CLONG BATTERY: 6 CELL, 7 CELL BATTERY PLAC	SPUR GEAR:
SWAY BAR: INO, IYES - SIZE: I.050", I.060", I.070" I.080", IOTHER:	